

FERTILIZER SPREADER

FOUR SIZES
PAYLOADS UP TO 21,000 LBS



FARMERS TALK, WE LISTEN

Lanco Fertilizer Spreaders get the job done right. More user-friendly and requiring much less maintenance than comparable spreaders, Lanco Fertilizer Spreaders provide world-class performance and world-class features.

Precision Saves You More

Lanco Fertilizer Spreaders come with Priority Operational Control (POC). Specifically designed by Lanco to be more user-friendly, POC regulates material according to ground speed without the use of a press wheel.

- ✓ Can be used to unload material while stationary (hydraulic units only)
- ✓ No wheel slippage
- ✓ Low maintenance

POC also available on Lanco Litter & Lime Spreaders!

Built with corrosion-resistant #304 stainless steel, Lanco's Fertilizer Spreaders are built to last longer.



Lanco's Fertilizer Spreaders ground drive system includes a stainless steel, "positive" chain drive requiring less maintenance.

MADE IN LANCASTER COUNTY TO WORLD-CLASS STANDARDS

BETTER SPREADING MADE SIMPLE

717-556-4143

WWW.LANCOEQUIPMENT.COM

LANCO
Manufacturing, CO.

MORE HIGH QUALITY FEATURES COME STANDARD

Specifications	Model LS 820	Model LS 1750	Model LS 2040	Model LS 2720
Hopper Capacity - Heaped	87 cu. ft.	185 cu. ft.	222 cu. ft.	296 cu. ft.
Hopper Capacity - Struck	80 cu. ft.	170 cu. ft.	204 cu. ft.	272 cu. ft.
Empty Weight	1,875 lb.	2,540 lb.	3,250 lb.	4,560 lb.
Maximum Gross Weight	7,000 lb.	14,000 lb.	16,000 lb.	21,000 lb.
Overall Length	193"	216"	218"	228.5"
Overall Height	62"	78"	84"	84"
Overall Width	72.25"	92.25"	97"	97"
Hopper Length	94.5"	102"	125.75"	146"
Hopper Width	72.25"	92.25"	92.25"	92.25"
Wheel Track Width (Center to Center)	77"	77" *	80"	80"

* A narrow track version can be ordered with 5' 2" center to center wheel tread.



Our fertilizer spreaders use more stainless steel throughout, including painted stainless steel mid and rear cross members where other spreaders rust first.



Optional: Roll-Over Tarp



The easy to use metering system provides a full range of gate opening choices for greater delivery and depth control.



Optional: On Board Engine

STANDARD FEATURES

- ✓ Hydraulic or belt-driven spinners
- ✓ Bolt-on spinner attachment – easy removal and serviceability
- ✓ Leaf Spring suspension
- ✓ Ground drive apron
- ✓ Double spinner disk; (19" stainless, 3/16th" Steel plate)
- ✓ Heavy-duty hub
- ✓ Heavy-duty Clevis hitch
- ✓ Grade 304 stainless steel box and back end
- ✓ Tractor hydraulic or ground drive
- ✓ 2 rear stainless cross members in chassis prevent corrosion and prolongs chassis life
- ✓ And More!

BETTER SPREADING MADE SIMPLE

717-556-4143

WWW.LANCOEQUIPMENT.COM

LANCO
Manufacturing, CO.