

**HIGH OUTPUT,
HEAVY DUTY COMMERCIAL**

**FIVES SIZES UP TO
1,000 CUBIC FOOT CAPACITY**

SPREAD ALMOST ANYTHING



FARMERS TALK, WE LISTEN



We design our spreaders by listening carefully to what farmers say, then deliver extra value by using the highest quality materials with a firm commitment to uncompromising workmanship.

Lanco's High Output series is designed to live up to its name. With the ability to spread virtually any material, Lanco High Output Spreaders include five standard sizes ranging from 420 cubic foot capacity to 1,000 cubic foot capacity.

Twin webs allow for material to be fed out the 78"-wide opening and into the teeth of massive 18"-diameter horizontal beaters. From there, spinners spread your material evenly across the pattern. With such a wide width and no "V" in the sides, bridging is impossible. One look and you'll see the difference. Lanco High Output Spreaders deliver the value farmers want. How do we know? We asked.

MADE IN LANCASTER COUNTY TO WORLD-CLASS STANDARDS

BETTER SPREADING MADE SIMPLE

717-556-4143
WWW.LANCOEQUIPMENT.COM

**LANCO
SPREADERS**

MORE HIGH QUALITY FEATURES COME STANDARD



Specifications	Model LS-400	Model LS-500	Model LS-7000	Model LS-8500	Model LS-10000
Hopper Height	61.5 inches	61.5 inches	61.5 inches	61.5 inches	61.5 inches
Hopper Width	117 inches	117 inches	117 inches	117 inches	117 inches
Hopper Length	12 ft.	16 ft.	20 ft.	24 ft.	30 ft.
Hopper Capacity Heaped 16"*	420 Cubic Feet, 337 Bushels, 15.5 Cubic Yards	566 Cubic Feet, 455 Bushels, 21 cubic Yards	700 Cubic Feet, 562 Bushels, 26 Cubic Yards	850 Cubic Feet, 683 Bushels, 31.5 Cubic Yards	1000 Cubic Feet, 803 Bushels, 37 Cubic Yards
Hopper Capacity Struck Level	320 Cubic Feet, 257 Bushels, 12 Cubic Yards	430 Cubic Feet, 345 Bushels, 16 Cubic Yards	515 Cubic Feet, 414 Bushels, 19 Cubic Yards	650 Cubic Feet, 522 Bushels, 24 Cubic Yards	810 Cubic feet, 650 Bushels, 30 Cubic yards
Overall Height	12 ft.	12 ft.	12 ft.	12 ft.	12 ft.
Overall Width	117 Cubic Inches	117 Cubic Inches	117 Cubic Inches	117 Cubic Inches	117 Cubic Inches
Overall Length	23'8"	27'8"	31'8"	35'8"	43'
Suspension	Walking Beam	Walking Beam	Heavy Duty Spring	Heavy Duty Spring	Tri Axle
Capacity	17 tons	17 tons	20 tons	20 tons	30 tons
Recommended Minimum Horsepower	250	250	250	270	300

*When Using Standard 4.25x65R22.5 Truck Tires

**Depending Upon Desired Tons/Acre, Material Composition and Travel Speed, Larger Tractors May Be Necessary.

Unlike The Majority Of Our Spreaders The Commercial Grade High Outputs Use Heaped Capacity In The Model Numbers, This Is Due To The Competitors In This Segment Doing The Same And Wanting To Make It Easier For The Customer To Compare When It Comes Time To Decide Which Model Is Right For Them.

Standard Features	Options
Mechanical PTO Driven Spinners and Beaters (1,000 RPM), Tractor Hydraulic Web*	Digi-Star NT800i Scale System, Can Be Integrated With Existing Rate Control Systems To Provide Incredible Accuracy
4.25x65R22.5 Truck Tires	Flotation Tires 700/50R22.5 or 700/40
Transport Lights	Work Lights
2 Camera System For Monitoring Material and Spread Pattern	
25,000 lb Jack	
Single Caliper Hydraulic Disc Brakes	2nd Caliper For Brake System
Hydraulic Endgate	
304 Stainless Beater Teeth	
Double Web Chain	2 Foot Extension Side Silage Package



*Tractor Hydraulics Require 30 GPM To Operate.

BETTER SPREADING MADE SIMPLE

717-556-4143

WWW.LANCOEQUIPMENT.COM

LANCO
SPREADERS